




SANDBLASTING ACCESSORIES

FABRICATION
FRANÇAISE



SANDBLASTING / GRITBLASTING

NOZZLES

Nozzle type	Nozzle spray	Nozzle spray	Abrasive velocity	Ø Recommended hoses
Round nozzle		± 2 cm	300 km/h	Ø 20 x 33
Venturi nozzle		± 6 cm	450 km/h - Ø 25	Ø 20 x 33 / Ø 25 x 39
Long Venturi nozzle		± 10 cm	720 km/h - Ø 32	Ø 25 x 39 / Ø 32 x 48

Ø Nozzle	Air consumption*	Media consumption
3	17 CFM	60 kg / Hour
4	30 CFM	100 kg / Hour
5	45 CFM	160 kg / Hour
6	80 CFM	230 kg / Hour
8	130 CFM	300 kg / Hour
9,5	195 CFM	544 kg / Hour
11	255 CFM	750 kg / Hour
12	335 CFM	950 kg / Hour

* Air consumption values are indicative. Add air losses in load, helmet air consumption and nozzle's abrasion.

Silicium carbide



Small thread Ø 29

Round

B 123 Ø 3 mm
B 124 Ø 4 mm
B 125 Ø 5 mm
B 126 Ø 6 mm
B 128 Ø 8 mm



Small thread Ø 29

Venturi

B 134 Ø 4 mm
B 135 Ø 5 mm
B 136 Ø 6 mm
B 138 Ø 8 mm

Boron carbide



Small thread Ø 29

Round

B 153 Ø 3 mm
B 154 Ø 4 mm
B 155 Ø 5 mm
B 156 Ø 6 mm
B 158 Ø 8 mm




Large thread Ø 50

Venturi

B 188 Ø 8 mm L. 167 mm
B 190 Ø 10 mm L. 167 mm
B 191 Ø 11 mm L. 200 mm

Silicium nitride



Large thread Ø 50

Long Venturi

B 165 Ø 5 mm L. 115 mm
B 166 Ø 6 mm L. 140 mm
B 168 Ø 8 mm L. 150 mm
B 169 Ø 9,5 mm L. 175 mm
B 171 Ø 11 mm L. 205 mm
B 172 Ø 12 mm L. 235 mm

Ceramic



S 903 Ø 3 mm L. 95 mm
S 904 Ø 4 mm L. 95 mm
S 905 Ø 5 mm L. 95 mm
S 906 Ø 6 mm L. 95 mm
S 908 Ø 8 mm L. 95 mm



S 802 Ø 2 mm L. 30 mm
S 803 Ø 3 mm L. 30 mm
S 804 Ø 4 mm L. 30 mm

NOZZLE-HOLDERS

Threaded nozzle-holder



Thread Ø 29
S 969 - For blast hose Ø 13 x 27
S 966 - For blast hose Ø 20 x 33



Thread Ø 50
S 967 - For blast hose Ø 25 x 39
S 971 - For blast hose Ø 20 x 33



Thread Ø 50
S 968 - For blast hose Ø 32 x 48

Ceramic nozzle-holder



S 997 - For small thread Ø 29



S 960 - For thread 1/4"


Adaptor




C 058 - Change from large thread Ø 50 for long venturi nozzle to small thread Ø 29 for round or venturi nozzle.

ACCESSORIES

Coupling for blast hose



BLAST COUPLING
S 862 - For blast hose Ø 20 x 33



BLAST COUPLING
S 964 - For blast hose Ø 25 x 39
S 965 - For blast hose Ø 32 x 48



QUICK COUPLING
S 962 - For blast hose Ø 13 x 27
S 963 - For blast hose Ø 20 x 33

Exit blaster coupling



S 160 - Male outlet 1 1/4
S 161 - Male outlet 1'




S 162 - Female outlet 1 1/4

Media flow valve



S 898
Manual valve 1 1/4



S 812
Ball valve 1/2

Air pressure regulator



S 101
Air flow
6 000 lit/min
(210 CFM)

BLAST HOSES



Blast hose with blast coupling and threaded nozzle-holder.

S 866	Ø 20 x 33	L. 10 m	S 937	Ø 32 x 48	L. 10 m
S 868	Ø 20 x 33	L. 20 m	S 938	Ø 32 x 48	L. 20 m
S 935	Ø 25 x 39	L. 10 m	S 807	Ø 20 x 33	L. 10 m
S 936	Ø 25 x 39	L. 20 m	S 808	Ø 20 x 33	L. 20 m



Blast hose extension with 2 blast couplings.

S 842	Ø 20 x 33	L. 10 m	S 845	Ø 25 x 39	L. 20 m
S 843	Ø 20 x 33	L. 20 m	S 846	Ø 32 x 48	L. 10 m
S 844	Ø 25 x 39	L. 10 m	S 847	Ø 32 x 48	L. 20 m



Blast hose with coupling and threaded nozzle-holder.

S 430	Ø 13 x 21	L. 5 m	S 865	Ø 20 x 33	L. 5 m
S 836	Ø 13 x 27	L. 5 m	S 933	Ø 20 x 33	L. 10 m
S 839	Ø 13 x 27	L. 10 m	S 934	Ø 20 x 33	L. 20 m



Blast hose with quick couplings.

S 914	Ø 20 x 33	L. 10 m	S 916	Ø 20 x 33	L. 20 m
--------------	-----------	---------	--------------	-----------	---------

Air hose with quick couplings.

T 110	Ø 19 x 29	L. 10 m	T 120	Ø 19 x 29	L. 20 m
--------------	-----------	---------	--------------	-----------	---------

Remote control extension Ø 4 x 6.

S 848	2 x (Ø 4 x 6)	L. 10 m
S 849	2 x (Ø 4 x 6)	L. 20 m
S 852	3 x (Ø 4 x 6)	L. 10 m
S 854	3 x (Ø 4 x 6)	L. 20 m
S 894	2 x (Ø 4 x 6) elders	- L. 10 m
S 896	2 x (Ø 4 x 6) elders	- L. 20 m

Your nearest dealer:



LE SPÉCIALISTE

B.P. 23 - 69380 LOZANNE - FRANCE

Tél. : +33 (0)4 78 43 62 62

Fax : +33 (0)4 78 43 69 28

E-mail : acf@acf-france.com

www.acf-france.com